



# KMR GAS OPERATED D-HEAD NAILER

## SPECIFICATION SHEET

### Properties

- Handy and well balanced
- With penetration depth adjustment
- Powerful driving
- Integrated rafter holder
- Anti-slip nosepiece
- Protective cap for sensitive surfaces

### Applications

Carpenters, roofers, timber frame construction. e.g. for fastening boards, roof battens, crates, pallets, visible boarding with oval head nails and nail screws

### KMR Strip nails P34° D-head


Diameter 2.6 - 3.1 mm  
Length 50-90mm




### Technical Data

Type Description	3890
Article Code	12100587
Length/ Height/ Width in mm	374/378/108
Weight	3.4kg
Magazine Type	Rear loader
Safety System	Single sequential actuation
Fastner Type	KMR strip nails P34°D-head
Diameter	2.6 - 3.1mm
Length	50-90mm
Magazine Capacity	60 Nails
Recommended shot per minute	4500
Recommended shot per hour	1100
Emission sound pressure level workstation	LpA, 1s=94.5 dB
Single-shot emission sound pressure level	L Wa, 1s=108.1 dB
Vibration level as per ISO 8862-11 is	3.36m/s <sup>2</sup>

Subject to technical modifications



**KMR Strip nails P34° D-head**  
Diameter 2,6 - 3,1 mm  
Length 50 - 90 mm



**KMR Strip nails P34° D-head**  
Diameter 2,6 - 3,1 mm  
Length 50 - 90 mm

Description	D X L (mm)			MI/CAR	MI/PAL
KMR Strip nails P34° D-Head Smooth	2.8 x 50	H	BK	2.2	184.8
KMR Strip nails P34° D-Head Smooth	2.8 x 64	H	BK	2.2	184.8
KMR Strip nails P34° D-Head Smooth	2.8 x 70	H	BK	2.2	184.8
KMR Strip nails P34° D-Head Smooth	2.8 x 80	H	BK	2.2	158.4
KMR Strip nails P34° D-Head Smooth	3.1 x 90	H	BK	2.2	158.4
KMR Strip nails P34° D-Head Smooth	2.8 x 64	H	GALV	2.2	184.8
KMR Strip nails P34° D-Head Smooth	2.8 x 70	H	GALV	2.2	184.8
KMR Strip nails P34° D-Head Smooth	2.8 x 80	H	GALV	2.2	158.4
KMR Strip nails P34° D-Head Smooth	3.1 x 80	H	GALV	2.2	158.4
KMR Strip nails P34° D-Head Smooth	3.1 x 90	H	GALV	2.2	158.4
KMR Strip nails P34° D-Head Ring	2.8 x 64	H	BK	2.2	184.8
KMR Strip nails P34° D-Head Ring	2.8 x 70	H	BK	2.2	184.8
KMR Strip nails P34° D-Head Ring	2.8 x 75	H	BK	2.2	158.4
KMR Strip nails P34° D-Head Ring	2.8 x 80	H	BK	2.2	158.4
KMR Strip nails P34° D-Head Ring	3.1 x 90	H	BK	2.2	158.4
KMR Strip nails P34° D-Head Ring	2.8 x 64	H	GALV	2.2	184.8
KMR Strip nails P34° D-Head Ring	2.8 x 70	H	GALV	2.2	184.8
KMR Strip nails P34° D-Head Ring	2.8 x 75	H	GALV	2.2	158.4
KMR Strip nails P34° D-Head Ring	2.8 x 80	H	GALV	2.2	158.4
KMR Strip nails P34° D-Head Ring	3.1 x 90	H	GALV	2.2	158.4

**Other Types and dimensions available upon request**

**References:**

H - resinated    BK - steel, bright    GALV - galvanised