

FORGE KNOT

RAILWAY DOG/CATTLE/FORGE KNOT

SPECIFICATION SHEET



- Requires fewer posts. Up to 50% saving material and labour costs
- High tensile strength and one piece vertical wire almost acts as its own intermediate enabling you to erect intermediate posts further apart, in most cases 4.5m to 6m ctrs

Summary of Features

- 24% stronger knot
- One Piece vertical wire, almost eliminates vertical wire movement from livestock pressure.

Specifications

- Manufactured to BS EN 10223-5
- Galvanised to BS EN 10244-2 Class A
- 450mm Pre-stripped ends, makes tying and joining easier
- Gauge: 2.5mm
- Tensile wire strengths -
- Horizontals: 1250-1350 (N/mm²)
- Verticals: 700-850 (N/mm²)
- Knots 500 (N/mm²)



Mesh Pattern

	mm	mm
7"	178	1218
6"	152	1040
6"	152	888
6"	152	736
5"	127	584
5"	127	457
4"	102	330
3"	76	228
3"	76	152
3"	76	76

150mm ctrs

Specification	Horizontal Wires	Vertical Spacings (cm)	Height (cm)	Roll Lengths (m)	Weight (kg)	Code
FHT11-122-15	11	15	122	50m	39.68kg	F2403F
				100m	79.36kg	F2404F