

ONDULINE RIDGE

SPECIFICATION SHEET

Ridge 2000 CLASSIC DR

Product Characteristics

Length	2000mm
Width	485mm
Thickness	2.9mm
Corrugation height	38mm
Pitch of corrugation	Non applicable
Weight per m ²	2.7kg/m ²
Weight	2.65kg
Surface	0.97m ²



Technical Data

Mechanical & physical properties

Bending under downward load	Not applicable
Impact strength	Not applicable
Tearing strength	< 150 N
Water impermeability	Pass ¹
Proportion of bitumen	> 40%
Homogeneity	Pass ²
Water absorption	< 20%

¹No drop of water underneath sheet after 48 hours

²No area larger than 1 cm² without bitumen

General Information

Application field

- Lightweight accessory designed for corrugated roofing sheets, specially in hot and humid climates.

Material description

- Bitumen material reinforced with cellulosic fibers and thermosetting resin. The composite is coloured with inorganic pigments.

Color range

- Available in black, green and translucent.
- Red and brown is subject to availability, please call 03330 050115 to find out more.

Installation

- Special conditions of installation are required. Refer to the installation guide.

Durability

Water impermeability after ageing	Pass ¹
Tearing strength after ageing	< 150 N
Thermal coefficient	< 100.10-6 1/K

Fire performance

Reaction to fire - EN 13501-1	E
-------------------------------	---