

HEAVY DUTY HIGH TENSILE BARBED WIRE

SPECIFICATION SHEET

- Supplied on wooden reels for strength and ease of disposal, and with hessian handles to be easier to carry.
- Ideal for use on top or bottom of stock fencing, use as a three or five strand cattle fence or for use with security fencing.
- Uses thicker line wires than standard high tensile barbed wire for added strength and durability.



Coating	Line wire dia (mm) & Tensile Strength of Line Wire (N/mm ²)	Barb dia & Tensile Strength (mm) / (N/mm ²)	Roll Length (m)	Average Weight per roll (kg)	Code
Bezinal coated	2.0mm dia - 1050-1250 N/mm ²	1.9mm dia - tensile strength 440-540 N/mm ²	200m	16.0kg	F2018
			500m	38.0kg	F2013
Galvanised Steel	2.0mm dia - 1050-1250 N/mm ²	1.9mm dia - tensile strength 440-540 N/mm ²	200m	15.7kg	F2014
			2000m	160kg	F2015
	1.6mm dia - 1050-1200 N/mm ²	1.45mm dia - tensile strength 415-495 N/mm ²	200m	10.9kg	F2010

Mild heavy galvanised also available - F2000

Bezinal coated - black tip barbs available



Bezinal Coated

- Exceeds BSEN 10244-2 Class A

Galvanised Steel

- Galvanised to BS EN 10244-2 Class A
- Manufactured to BS EN 10223-1

Other patterns, sizes and lengths can be made on request.

Copyright © 2020 McVeigh Parker. All Rights Reserved.